

CLAIMS

1. An entry door security brace for impeding forced entry into a room through a door, said door having a lockset with a pair of knobs on opposite side surfaces of the doors, the knobs being operatively coupled to a shaft, said brace comprising:

- a) a plurality of pole members wherein said pole members include an upper end, and lower end with a foot member secured to the lower end of said pole member; and
- b) a block member secured to the upper ends of said plurality of pole members, said block member having a top planar surface with a yoke extending upward from the top planar surface, said yoke adapted to receive said shaft.

2. The security brace in claim 1 where the plurality of pole members each comprise first and second tubular telescoping segments and means for locking said segments relative to one another at a predetermined composite length.

3. The security brace in claim 1 wherein the pole members are secured to the block member by a plurality of circular apertures in a bottom surface of the block, wherein the pole members pass through the apertures and said pole members are held in the block member by a locking member.

4. The security brace in claim 1 wherein said foot member includes a non-skid floor engaging surface.

5. The security brace in claim 4 wherein said non-skid surface is an elastomeric pad.

6. The security brace in claim 4 wherein said non-skid surface includes a plurality of downwardly projecting corrugations.

7. The security brace in claim 1 wherein the yoke is attached to a block member by a cylindrical stem extending upwardly from the top surface for fitting into a circular opening in the bottom of the yoke.